

Fabrics

MultiFLEX Datasheet

Description:	MultiFLEX is a Premium Quality 670GSM medium to heavy duty reinforced PVC using a plain weave base cloth. Developed by HVG using the highest quality resins, UV Stabilisers & Fire Retardant inhibitors.
Application:	Tarps, Sporting Equipment, Canopies, Camper Trailers, Container Curtains, Promotional Tents, Swags, Tent Floors & many other general purpose applications.
Weight:	670GSM
Width:	250cm
Roll Length:	30m
Composition:	Reinforced PVC
Colours:	Red, Black, Royal Blue, Green, Dark Grey, White
Coating:	Spread coated PVC
Tensile Strength:	Warp 3000N/5cm, Weft 2800N/5cm
Tear Strength:	Warp 540N/5cm, Weft 510N/5cm
Weld Adhesion:	105N/5cm
Temperature Range:	-30°C +70°C
UV Stabilised:	Yes – UV Stabilised scrim and coating
Warranty:	Yes – 3 Year UV Warranty
Fire Rated NFPA 701-2004:	Yes – Test results available on request. *Manufacturers laboratory tests show when the ignition source Is removed the fabric immediately self-extinguishes.
AS/NZS 1530.3-1999:	Yes – Test results available on request.

Product Performance and Suitability: All of the descriptive information and recommendations for use of this product shall only be used as a guide. Furnishing such information in no event constitutes a warranty of any kind. Buyers shall independently test and determine the suitability of the material for the purpose for which it is intended. No one is authorised to give any warranty, guarantee or make any representation in addition or contrary to the above.

