



Care & Cleaning Instructions for FLEX™ PVC

The premium quality coated PVC range of FLEX products were developed exclusively by HVG Fabrics using the highest quality resins, UV stabilisers and fire retardant inhibitors. Good self-extinguishing properties as well as an attractive easy clean high-gloss surface make them the ideal choice for a multitude of applications. With extreme tear and tensile characteristics, superior welding capabilities and a market leading 5 year UV warranty the FLEX range of PVC's are the product of choice.

To help ensure the maximum life from FLEX PVC the following tips should be observed:

- Keep the fabric clean by brushing regularly both sides of the fabric using a soft-bristle brush and hosing occasionally with clear and cold water.
- Do not apply detergents, cleaning fluids, soaps or any types of insecticides and garden sprays.
- Do not allow foreign matter; dirt, bird droppings, tree sap etc, to remain in contact with the fabric.
- Do not allow petrochemicals or solvents to come into contact with the fabric.
- Avoid harsh scrubbing or rubbing otherwise the surface of the fabric may damage.
- Before stowing away your shade solution, ensure that the fabric is thoroughly dry.

Removing stubborn stains:

- Mix a weak concentration of household PH neutral detergent (1:20 ratio) in lukewarm water. The detergent must not contain solvents.
- Apply the detergent and water mix to the fabric using a soft cloth, sponge, soft-bristle brush or soft mop. After cleaning, rinse off ALL residue with plenty of fresh clear, cold water.

Preventing the spread of mildew:

- Mix diluted chlorine bleach (1:20 ratio) in lukewarm water, then rinse off ALL residues with plenty of fresh clear, cold water.

Halifax Vogel Group takes no responsibility for the performance of any cleaning agent or potential damage caused by the use of such. These cleaning instructions are universal for PVC fabrics and are to be used as a guide only.