



CoverFLEX™ FR Datasheet

| | |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Description: | CoverFLEX™ FR is a premium quality 610gsm spread coated PVC with gloss acrylic lacquer developed by HVG using the highest quality resins, UV stabilisers & fire retardant inhibitors. |
| Application: | Grain bunker covers, tarpaulins, camper trailers, sports equipment, swags, promotional tents, container curtains as well as most outdoor and indoor cover applications. |
| Weight: | 610GSM |
| Width: | 205cm, 250cm, 300cm, 320cm |
| Roll Length: | 30m (200m available on request). |
| Construction: | 1100 dtex x 1100 dtex, 20 x 20 per square inch. |
| Base Cloth: | HT polyester scrim. |
| Coating: | Spread coated PVC |
| Fabric Finish: | Gloss acrylic lacquered both sides. |
| Colours: | White, Grey, Dark Grey, Charcoal, Yellow, Red, Black, Dark Blue, Green. |
| Tensile Strength: | Warp 2400N/5cm Weft 2400N/5cm. |
| Tear Strength: | Warp 450N/5cm Weft 400N/5cm. |
| Weld Adhesion: | 120N/5cm. |
| Temperature Range: | -20°C +70°C |
| UV Resistant: | Yes – UV stabilized scrim and coating |
| Warranty: | Yes – 5 year UV Warranty |
| Fire Rated: | Yes. AS1530. Part 2, Part 3. NFPA 701-2004 *Manufacturers laboratory tests show when the ignition source is removed the fabric immediately self-extinguishes. |

Product Performance and Suitability: All of the descriptive information and recommendations for use of this product shall only be used as a guide. Furnishing such information in no event constitutes a warranty of any kind. Buyers shall independently test and determine the suitability of the material for the purpose for which it is intended. No one is authorised to give any warranty, guarantee or make any representation in addition or contrary to the above.