



Tarpee™ M60 Datasheet

Description:	Tarpee™ M60 is a 60 micron coated woven PE using Metallocene on a single stacked scrim.
Applications:	Grain storage bunker covers, dam and pond liners. Agricultural covers. Dome, airplane, animal shelters and covers. Waterproof membranes and water storage liners.
Construction:	1440 (1300D) (denier)
Yarn(/sq. cm²):	14 x 14
Weave Style:	Single folded yarn.
Coating Thickness:	60 micron.
Total Thickness:	0.48mm.
Weight:	270 gsm.
Tensile Strength:	Warp 1677N/5cm Weft 1749N/5cm.
Tear Strength:	Warp 160N/5cm Weft 211N/5cm.
Metallocene:	Yes
Colours:	Blue, Beige
Roll Width:	205cm
Roll Length:	50m, 1000m, 1500m
Temperature:	-30°C to +70°C
R Values:	0.669.
Warranty:	Yes – 6 year UV Warranty.

Product Performance and Suitability: All of the descriptive information and recommendations for use of this product shall only be used as a guide. Furnishing such information in no event constitutes a warranty of any kind. Buyers shall independently test and determine the suitability of the material for the purpose for which it is intended. No one is authorised to give any warranty, guarantee or make any representation in addition or contrary to the above.