



## Tarpee™ Xtra Datasheet

<b>Description:</b>	Tarpee™ Xtra is a 65/60 micron coated woven PE using a heavy double stacked scrim.
<b>Applications:</b>	Larger shelter, dome and structural covers. Heavy duty tarpaulins, dam liners, water storage liners, landfill covers.
<b>Construction:</b>	3340 (3000D) (denier)
<b>Yarn(/sq. cm<sup>2</sup>):</b>	8 x 8
<b>Weave Style:</b>	Double stacked scrim
<b>Coating Thickness:</b>	65 micron top side / 60 micron underside
<b>Total Thickness:</b>	0.55mm
<b>Weight:</b>	330 gsm
<b>Tensile Strength:</b>	Warp 2100N/5cm Weft 1950N/5cm
<b>Tear Strength:</b>	Warp 450N/5cm Weft 420N/5cm
<b>Colours:</b>	White/Silver, White, Blue, Green
<b>Roll Width:</b>	205cm, 366cm
<b>Roll Length:</b>	100m, 500m, 1000m
<b>Temperature:</b>	-30°C to +70°C
<b>R Values:</b>	0.821
<b>Warranty:</b>	Yes – 7 year UV Warranty

**Product Performance and Suitability:** All of the descriptive information and recommendations for use of this product shall only be used as a guide. Furnishing such information in no event constitutes a warranty of any kind. Buyers shall independently test and determine the suitability of the material for the purpose for which it is intended. No one is authorised to give any warranty, guarantee or make any representation in addition or contrary to the above.