



## Tarpee™ Titan FR Datasheet

<b>Description:</b>	Tarpee™ Titan FR is a 90 micron topside, 60 micron underside coated woven PE using a heavy duty double stacked scrim.
<b>Applications:</b>	Dome and large span structures and shelters.
<b>Construction:</b>	4600 (4140D) (Denier).
<b>Yarn(/sq. cm<sup>2</sup>):</b>	8 x 8
<b>Weave Style:</b>	Double stacked scrim
<b>Coating Thickness:</b>	90 micron topside / 60 micron underside
<b>Total Thickness:</b>	0.65 mm
<b>Weight:</b>	415 gsm
<b>Tensile Strength:</b>	Warp 2600N/5cm Weft 2400N/5cm
<b>Tear Strength:</b>	Warp 410N/5cm Weft 430N/5cm
<b>Colours:</b>	White, White/Silver
<b>Roll Width:</b>	366cm
<b>Roll Length:</b>	100m, 500m
<b>Fire Rated:</b>	Yes -AS1530.2, AS1530.3 & JISL1091
<b>Temperature:</b>	-30°C +70°C
<b>R Values:</b>	0.866
<b>Warranty:</b>	Yes – 10 year UV Warranty

**Product Performance and Suitability:** All of the descriptive information and recommendations for use of this product shall only be used as a guide. Furnishing such information in no event constitutes a warranty of any kind. Buyers shall independently test and determine the suitability of the material for the purpose for which it is intended. No one is authorised to give any warranty, guarantee or make any representation in addition or contrary to the above.

CD0620