

HVG Fabrics Pty Ltd ABN: 30 649 411 763

hvgfabrics.com.au | p 1300 854 811

Tarpee™ M60 Datasheet

Description: Tarpee™ M60 is a 60 micron coated woven PE using Metallocene

on a single stacked scrim.

Applications: Grain storage bunker covers, dam and pond liners. Agricultural

covers. Dome, airplane, animal shelters and covers. Waterproof

membranes and water storage liners.

Construction: 1440 (1300D) (denier)

Yarn(/sq. cm²): 14 x 14

Weave Style: Single folded yarn.

Coating Thickness: 60 micron.

Total Thickness: 0.48mm.

Weight: 270 gsm.

Tensile Strength: Warp 1677N/5cm Weft 1749N/5cm.

Tear Strength: Warp 160N/5cm Weft 211N/5cm.

Metallocene:

Colours: Blue, Beige

Roll Width: 205cm

Roll Length: 50m, 1000m, 1500m

Temperature: -30°C to +70°C

R Values: 0.669.

Warranty: Yes – 6 year UV Warranty.

CD0923

Product Performance and Suitability: All of the descriptive information and recommendations for use of this product shall only be used as a guide. Furnishing such information in no event constitutes a warranty of any kind. Buyers shall independently test and determine the suitability of the material for the purpose for which it is intended. No one is authorised to give any warranty, guarantee or make any representation in addition or contrary to the above.

SYDNEY 29 Henderson Street Turrella NSW 2205 MELBOURNE 25 West Park Drive Derrimut VIC 3026 **BRISBANE** 128 Mica Street Carole Park QLD 4300

PERTH72 Bushland Ridge
Bibra Lake WA 6163

ADELAIDE 57 Barnes Avenue Marleston SA 5033

















