

HVG Fabrics Pty Ltd ABN: 30 649 411 763

hvgfabrics.com.au | p 1300 854 811

Tarpee™ Titan Datasheet

Tarpee™ Titan is a 90 micron topside, 60 micron underside coated woven **Description:**

PE using a heavy duty double stacked scrim.

Dome and large span structures and shelters. Water liners. Temporary Applications:

structures and shelters.

Construction: 4600 (4140D) (denier).

Yarn(/sq. cm²): 8 X 8

Weave Style: Double stacked scrim

Coating Thickness: 90 micron topside / 60 micron underside

0.62mm **Total Thickness:**

410gsm Weight:

Tensile Strength: Warp 2530N/5cm Weft 2857N/5cm.

Warp 609N/5cm Weft 641N/5cm. **Tear Strength:**

White, White/Silver Colours:

Roll Width: 366cm

100m, 500m Roll Length:

Burst Strength

(AS4878.7 - Method B):

Hydrostatic Pressure

(AS2001.2.17):

>250kPA.

5300kPA

Temperature: -30°C to +70°C

0.866 R Values:

Warranty: Yes – 10 year UV Warranty

CD0923

Product Performance and Suitability: All of the descriptive information and recommendations for use of this product shall only be used as a guide. Furnishing such information in no event constitutes a warranty of any kind. Buyers shall independently test and determine the suitability of the material for the purpose for which it is intended. No one is authorised to give any warranty, guarantee or make any representation in addition or contrary to the above.

SYDNEY 29 Henderson Street

MELBOURNE 25 West Park Drive Turrella NSW 2205 Derrimut VIC 3026

BRISBANE 128 Mica Street Carole Park QLD 4300

72 Bushland Ridge Bibra Lake WA 6163 **ADELAIDE** 57 Barnes Avenue Marleston SA 5033

















