



Tarpee™ Xtra Datasheet

Description:	Tarpee™ Xtra is a 65/60 micron coated woven PE using a heavy double stacked scrim.
Applications:	Larger shelter, dome and structural covers. Heavy duty tarpaulins, dam liners, water storage liners, landfill covers.
Construction:	3340 (3000D) (denier)
Yarn(/sq. cm²):	8 x 8
Weave Style:	Double stacked scrim
Coating Thickness:	65 micron top side / 60 micron underside
Total Thickness:	0.55mm
Weight:	330 gsm
Tensile Strength:	Warp 2100N/5cm Weft 1950N/5cm
Tear Strength:	Warp 450N/5cm Weft 420N/5cm
Colours:	White/Silver, White, Blue, Green
Roll Width:	205cm, 366cm
Roll Length:	100m, 500m, 1000m
Temperature:	-30°C to +70°C
R Values:	0.821
Warranty:	Yes – 7 year UV Warranty

CD0923

Product Performance and Suitability: All of the descriptive information and recommendations for use of this product shall only be used as a guide. Furnishing such information in no event constitutes a warranty of any kind. Buyers shall independently test and determine the suitability of the material for the purpose for which it is intended. No one is authorised to give any warranty, guarantee or make any representation in addition or contrary to the above.

SYDNEY
29 Henderson Street
Turrella NSW 2205

MELBOURNE
25 West Park Drive
Derrimut VIC 3026

BRISBANE
128 Mica Street
Carole Park QLD 4300

PERTH
72 Bushland Ridge
Bibra Lake WA 6163

ADELAIDE
57 Barnes Avenue
Marleston SA 5033

